

# Die cutting products by Koskisen plywood

## KoskiLaser

- Uncoated Finnish birch panel glued for laser cutting
- Thicknesses: 4–24 mm
- Standard panel sizes: 1250 x 2500 mm, 1525 x 3050 mm
- Standard face quality BB/BB

## KoskiLaser Eco

- Finnish birch plywood specially glued for laser cutting
- Thicknesses: 6.5, 9, 12, 15, 18, 21 and 24 mm
- Standard panel sizes: 1250 x 2500 mm, 1525 x 3050 mm
- Treated with a translucent water based agent in custom colours

## KoskiLaser Transparent

- Coated Finnish birch plywood glued for laser cutting
- Thicknesses: 9–24 mm
- Standard panel sizes: 1250 x 2500 mm, 1525 x 3050 mm
- Coated with hard wearing transparent melamine

## KoskiLaser 3D

- Smooth surfaced Finnish birch plywood produced with Power Orientated Micro Multiplex Stabiliser (POMMS) technology
- Thicknesses: 16 mm and 18 mm
- Standard panel size: 1525 x 2440 mm
- Coated with a silver laminate



Koskisen  
 Tehdastie 2 | 16600, Järvelä  
 p. 020 553 41 | info@koskisen.com



2412-CPR-1301-01



PEFC02-34-12



FSC  
 www.fsc.org  
 FSC® C116522