



Thickness mm	> 6-13	> 13-20	> 20-25	> 25-32	> 32-40
Bending Strength (N/mm <sup>2</sup> )	10,5	10	10	8,5	7
Internal Bond (N/mm <sup>2</sup> )	0,28	0,24	0,20	0,17	0,14

Essential characteristics	Performance	Standard
Release of formaldehyde	E1 (E0.5 on request)	(BS) EN 13986
Reaction to fire	D-s2, d0	
Water vapour permeability	3...7x10 <sup>-12</sup> kg/msPa	
Airborne sound insulation	NPD	
Sound absorption	NPD	
Thermal conductivity	0,13 W/(m k)	
Impact Resistance	NPD	
Mechanical Durability	Table 3.1	
Detailed information can be found in Tables 3.1 & 3.2 of (BS) EN 1995-1-1	Table 3.2	
Biological durability (BS) EN 335	Class 1	
Content of pentachlorophenol (PCP)	≤ 5 ppm	

The performance of the product identified in point 1. is in conformity with the declared performance in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and behalf of the manufacturer 07.11.2024.

*Santtu Eilamo*  
Santtu Eilamo  
Quality Manager, Panel Industry



: **Koskisen**  
 : Tehdastie 2 | 16600, Järvelä, Finland  
 : +358 20 553 41 | info@koskisen.com  
 : VAT No FI0148241-9 | Reg. Office Kärkölä