

# KoskiFloor



## Floor board of high quality and durability

KoskiFloor is an all round tongued and grooved floor board ideal for new buildings and repair work. The boards are made of the by-products from wood industries and they preserve the same desirable features of wood.

With KoskiFloor products it is easy and quick to make durable floors that feel pleasant in use. The boards can be sawn, drilled and cut with any conventional woodworking tools.

KoskiFloor standard board grade P6 is ideal for floors in dry conditions. For more demanding conditions, we recommend KoskiFloor P5/P6 board that meets the strength requirements of P6 grade and the moisture conditions of P5 grade.

KoskiFloor is suitable especially for floors of housing, floating floors, floors of storerooms and roof support boards (P5).



EASY TO USE



EASY  
MACHINING



ECO-  
FRIENDLY



ACOUSTIC



Quick installation



Good sound-insulating properties



Easy to work and coat



Environmentally friendly



Solid and dense surface



The strength of the board is constant in every direction



**KOSKISEN**

# KoskiFloor



## Technical specifications

<b>Raw material</b>	Saw dust and wood chips from our own wood industry
<b>Base board</b>	Chipboard to meet standard EN 312
<b>Formaldehyde class</b>	Class E1 EN 312 Class E0,5 EN 312 and CARB/TSCA for P6 on request
<b>Thickness</b>	Standard thickness 22, Other at request
<b>Sizes</b>	Standard sizes 600 x 1800/2400, 1200 x 2400 mm. Other sizes at request.
<b>Density</b>	Depends on the thickness and type of the board 620-720 kg/m <sup>3</sup> (P6), 680-765 kg/m <sup>3</sup> (P5)
<b>Installation</b>	Installation instructions and other information can be found in the standard EN 312 and at <a href="http://www.koskisen.com">www.koskisen.com</a>
<b>Machining</b>	Drilling of holes edge machining like T&G, chamfer and rebate on request.
<b>Other data</b>	Detailed technical values can be found in Koskisen's Declaration of Performance (DoP). Please visit <a href="http://koskisen.com/download">koskisen.com/download</a> .

### Pallet sizes

Thickness	Size	Pcs / pll
22	1200x2400	25
	600x2400	50
	600x1800	50

### T&G alternatives

All four edges T&G max size 1800 x 4000 mm  
Two long edges T&G max size 1800 x 4200 mm



TG 16-30 mm



FTG 30-40 mm



DTG 22-25 mm

## Additional information

### Environment

Our raw material, wood is an ecological and renewable material and it stores carbon during its whole life cycle. Koskisen chipboard products are manufactured in Finland according to the strictest sustainability principles. Koskisen is a pioneer in the Finnish forest industry in paying attention to the environment and the wood's supply chain is always known in detail. Finnish forests are primarily privately owned and the owners are guided by a strong commitment to long-term forestry and forest cultivation. Yearly, Finnish forests grow more than they are harvested. This guarantees a sustainable and environmentally sound raw material.

### Additional information

Koskisen chipboard is made from our own sawmill's sawdust and contains 85% real wood. Our professional quality control ensures that Koskisen chipboard is always pure and does not include sand or other impurities. Pure and high-quality chipboard is easy to machine and it doesn't damage saw blades.

The information, although based on extensive testing, is intended as a guideline only and comes without warranty. We reserve the right to amend specifications without notice. Any defects other than those caused by clearly verified production or service faults by the supplier are the responsibility of the user. Any claim for compensation is limited to the value of the defective panels. The Seller makes no guarantee that the goods are fit for a particular purpose, unless it provides a written declaration of their suitability.



### Koskisen Panel Industry

Tehdastie 2, 16600 Järvelä, FINLAND  
tel. +358 20 553 41  
[koskisen.com](http://koskisen.com)

