

KoskiFloor



Floor board of high quality and durability

KoskiFloor is an all round tongued and grooved floor board ideal for new buildings and repair work. The boards are made of the by-products from wood industries and they preserve the same desirable features of wood.

With KoskiFloor products it is easy and quick to make durable floors that feel pleasant in use. The boards can be sawn, drilled and cut with any conventional woodworking tools.

KoskiFloor standard board grade P6 is ideal for floors in dry conditions. For more demanding conditions, we recommend KoskiFloor P5/P6 board that meets the strength requirements of P6 grade and the moisture conditions of P5 grade.

KoskiFloor is suitable especially for floors of housing, floating floors, floors of storerooms and roof support boards (P5).



EASY TO USE



EASY
MACHINING



ACOUSTIC



Quick installation



Good sound-insulating properties



Easy to work and coat



Solid and dense surface



The strength of the board is
constant in every direction



KOSKISEN

KoskiFloor



Technical specifications

Raw material	Saw dust and wood chips from our own wood industry
Base board	Chipboard to meet standard EN 312
Formaldehyde class	Class E0,5 EN 312, CARB/TSCA on request
Thickness	Standard thickness 22, Other at request
Sizes	Standard sizes 600 x 1800/2400, 1200 x 2400 mm. Other sizes at request.
Density	Depends on the thickness and type of the board 620-720 kg/m ³ (P6), 680-765 kg/m ³ (P5)
Installation	Installation instructions and other information can be found in the standard EN 312 and at www.koskisen.com
Machining	Drilling of holes edge machining like T&G, chamfer and rebate on request.
Other data	Detailed technical values can be found in Koskisen's Declaration of Performance (DoP). Please visit Koskisen website.

Pallet sizes

Thickness	Size	Pcs / pll
22	1200x2400	25
	600x2400	50
	600x1800	50

T&G alternatives

All four edges T&G max size 1800 x 4000 mm
Two long edges T&G max size 1800 x 4200 mm



TG 16-30 mm



FTG 30-40 mm



DTG 22-25 mm

Sustainability

Koskisen's products are safe for their intended use and comply with all applicable quality, environmental, and product requirements. The focus areas of product development are improving the long service life, renewability, safety, and traceability of products.

Read more: koskisen.com/sustainability

Additional information

Koskisen chipboard is made from our own sawmill's sawdust and contains 90% real wood. Our professional quality control ensures that Koskisen chipboard is always pure and does not include sand or other impurities. Pure and high-quality chipboard is easy to machine and it doesn't damage saw blades.

The information, although based on extensive testing, is intended as a guideline only and comes without warranty. We reserve the right to amend specifications without notice. Any defects other than those caused by clearly verified production or service faults by the supplier are the responsibility of the user. Any claim for compensation is limited to the value of the defective panels. The Seller makes no guarantee that the goods are fit for a particular purpose, unless it provides a written declaration of their suitability.



Koskisen Panel Industry

Tehdastie 2, 16600 Järvelä, FINLAND
tel. +358 20 553 41
koskisen.com

