KoskiPaint



With ready surface for painting

KoskiPaint is Finnish birch plywood with one or two sides overlaid with special painting film. The thick, hot pressed coating gives a durable and uniform surface

The factory applied painting film makes painting easy, fast and provides for a smooth long lasting paint finish. For most applications only two coats are needed, which means considerable savings in costs. The board is suitable for interior and exterior use.

KoskiPaint is suitable especially for doors, interior cladding, farm building, vehicle bodies and sidewalls, signs and billboards and sporting equipment.

EASY TO PAINT

EASY TO USE

EASY MACHINING

- Easy painting
- Savings in painting costs and time
- Smooth and uniform paint finish
- Reduced risk of surface rippling and checking due to moisture variatons

KOSKISEN

KoskiPaint

Technical specifications

Base plywood	Koskisen Finnish birch plywood
Bonding	Phenolic resin according to EN 314-2/ class 3 exterior conditions. Formaldehyde emission levels of panels fulfil REACH requirements <= 0,062 mg/m3 (EN 717-1) Class E05 CARB Phase II, ULEF (Ultra Low Emitting Formaldehyde)
Coating	Fully exterior phenolic resin based precured painting film with a total weight of 300 g/m2
Standard thicknesses	6,5, 9, 12, 15, 18, 21, 24, 27 and 30 mm
Standard sizes	1200/1220/1250 x 2400/2440/2500 mm 1500/1525 x 3000/3050 mm Other sizes on request
Density	Approx 700 kg/m3
Edge treatment	Acrylic paint against moisture pick up
Machining	Drilling of holes edge machining like T&G, chamfer and rebate on request.
Other data	Detailed technical values can be found in Koskisen's Declaration of Performance (DoP). Please visit Koskisen website.

Sustainability

Koskisen's products are safe for their intended use and comply with all applicable quality, environmental, and product requirements. The focus areas of product development are improving the long service life, renewability, safety, and traceability of products. Read more: koskisen.com/sustainability

Additional information

Wood is a living material and every panel is unique. Therefore a photograph or a sample piece cannot represent a full sized panel as regards colours, shades, figure, knots etc. Please note that a slight colour variation is accepted between panels.

The information, although based on extensive testing, is intended as a guideline only and comes without warranty. We reserve the right to amend specifications without notice. Any defects other than those caused by clearly verified production or service faults by the supplier are the responsibility of the user. Any claim for compensation is limited to the value of the defective panels. The Seller makes no guarantee that the goods are fit for a particular purpose, unless it provides a written declaration of their suitability.

Koskisen Panel Industry
Tehdastie 2, 16600 Järvelä, FINLAND
tel. +358 20 553 41
koskisen.com

FSC® C116522 PEFC/02-31-235 2412-CPR-1301-01