KoskiPly Standard



Multipurpose plywood

KoskiPly Standard thin plywood sheets are made from rotary cut birch veneers. As surface veneer, 0.5 mm thick rotary cut, unpatched sound surface veneer. 1.5 mm thick rotary cut veneers are used as core veneers.

The veneers are laid in such a way that the grain directions of the overlapping veneers are perpendicular to each other. Cross lamination makes plywood strong and therefore suitable for many applications.







EASY TO USE

- Homogeneous surface of a consistent high quality
- High quality birch plywood for many applications
- Easy to work

- Versatile panel for multi-use
- Smooth surface quality







Technical specifications

| Bonding | Exterior and interior as standard. |
|-------------------------|---|
| Face qualities | Rotary cut birch veneer, without joints. Standard face quality options S/BB (AB/B) BB/BB (B/B) |
| Standard thicknesses | 4 mm - 4 ply 7 mm - 6 ply |
| Standard sizes | Interior 1220 x 2440 mm / 2440x1220 mm Exterior 1220 x 2440 mm / 2440x1220 mm |
| Density Approx. | approx. 700 kg/m3 |

Sustainability

Koskisen's products are safe for their intended use and meet the quality, environment and product specific requirements set for them. Product development emphasises the development of responsible and sustainable product features. The focus is on improving the long-term use, renewability, safety, and traceability of products. Read more: koskisen.com/sustainability

Additional information

Wood is a living material and every panel is unique. Therefore a photograph or a sample piece cannot represent a full sized panel as regards colours, shades, figure, knots etc. Please note that a slight colour variation is accepted between panels.

The information, although based on extensive testing, is intended as a guideline only and comes without warranty. We reserve the right to amend specifications without notice. Any defects other than those caused by clearly verified production or service faults by the supplier are the responsibility of the user. Any claim for compensation is limited to the value of the defective panels. The Seller makes no guarantee that the goods are fit for a particular purpose, unless it provides a written declaration of their suitability.





