

KoskiBond F



EN 45545-2

KoskiBond F is a birch plywood panel offering new features such as fire-resistance combined with strong bonding properties. KoskiBond F is made of Finnish birch plywood and is designed to provide safe floor solutions. The faces of the board are coated with a specially designed overlay, which provides greater fire protection combined with high bond strength.

The combined possibilities of improved fire-resistance, excellent bonding strength and high quality birch plywood provide a solution for the innovative design and construction of vehicles for the passenger transport industry, such as railcar floors, bus floors and more.

KoskiBond F is suitable especially for train's and tram's floors.



EASY
MACHINING



ECO-
FRIENDLY



EASY TO USE



FIRE
RESISTANT



BONDING
STRENGTH



LOW
EMISSION

-  Improved fire-resistant properties fulfilling the demanding requirements of EN 45545-2(08/2013)
-  Multiple use - surfaces can be painted or overlaid
-  Achieves R10 the Hazard Level HL3
-  High-quality, Koskisen birch plywood, strong and durable, light and dimensionally stable
-  Functional surface to obtain perfect bond strength with structural adhesives, e.g. polyurethane/epoxy adhesive and others.
-  Smooth and durable surface



KOSKISEN

KoskiBond F



Technical specifications

Base plywood	Koskisen Finnish birch plywood
Bonding	Phenolic resin according to EN 314-2/ class 3 exterior conditions Formaldehyde emission levels of panels fulfil requirements of Class E1 (EN13986), CARB Phase II, ULEF (Ultra Low Emitting Formaldehyde)
Coating	Customised, functional overlays
Standard thicknesses	4-30 mm
Standard sizes	1250 x 2500 mm 1525 x 3050 mm Other sizes on request.
Density	Approx 700 kg/m ³
Edge treatment	Standard without edge sealing, available on request.
Fire classifications	The fire-resistance properties of KoskiBond F has been tested by RST. DIN EN 45545-2 (08/2013) fulfills R10 Hazard level HL 3
Machining	Drilling of holes edge machining like T&G, chamfer and rebate on request.
Other data	Detailed technical values can be found in Koskisen's Declaration of Performance (DoP). Please visit koskisen.com/download .

Additional information

Environment

Our raw material, wood is an ecological and renewable material and it stores carbon during its whole life cycle. Koskisen plywood products are manufactured in Finland according to the strictest sustainability principles. Koskisen is a pioneer in the Finnish forest industry in paying attention to the environment and the wood's supply chain is always known in detail. Finnish forests are primarily privately owned and the owners are guided by a strong commitment to long-term forestry and forest cultivation. Yearly, Finnish forests grow more than they are harvested. This guarantees a sustainable and environmentally sound raw material.

Additional information

Wood is a living material and every panel is unique. Therefore a photograph or a sample piece cannot represent a full sized panel as regards colours, shades, figure, knots etc. Please note that a slight colour variation is accepted between panels.

The information, although based on extensive testing, is intended as a guideline only and comes without warranty. We reserve the right to amend specifications without notice. Any defects other than those caused by clearly verified production or service faults by the supplier are the responsibility of the user. Any claim for compensation is limited to the value of the defective panels. The Seller makes no guarantee that the goods are fit for a particular purpose, unless it provides a written declaration of their suitability.



Koskisen Panel Industry

Tehdastie 2, 16600 Järvelä, FINLAND
tel. +358 20 553 41
koskisen.com

