

KoskiPan



Uncoated standard chipboard

Koskisen chipboards are made from genuine wood. Wood accounts for 90 per cent of the boards. Clean raw material ensures that our boards are of high quality and easy to work.

KoskiPan is uncoated standard chipboard. The boards can be sawn, drilled and cut with any conventional woodworking tools.

The boards can be used to create a range of durable practical structures rapidly and inexpensively. The strength grades of KoskiPan are P1, P2, P4, P5 and P6. The uniform compact surface is an excellent base for different type of coatings.

KoskiPan is suitable especially for floors, internal walls and ceilings, fixtures, kitchens, bathrooms, laminate worktops, doors, panels, exhibition, shops and other special furniture and P5 quality for dry places outdoors.



EASY
MACHINING



EASY TO USE



ACOUSTIC



MULTI USE

+ Standard board with many possibilities

+ Easy to work

+ Wide range of sizes

+ Light surface colour

+ The strength of the board is constant in every direction

+ Good sound-insulating properties

+ CARB/TSCA for grades P1,P2, P2Mr, P4 & P5



KOSKISEN

KoskiPan

Technical specifications



Raw material	Saw dust and wood chips from our own wood industry
Base board	Chipboard to meet standard EN 312
Formaldehyde class	Class E1 EN 312 Class E0,5 EN312 for P2 & P2Mr on request CARB/TSCA for P1, P2, P2Mr, P4, P6 on request
Thickness	Stepless 4-50 mm
Sizes	1220 x 2630 mm, 1290 x 3045 mm, 1830 x 2630 mm, 1200-1830 x 1830-4580 mm. Other sizes at request.
Density	Depends on the thickness and type of the board 600-800 kg/m ³
Machining	Drilling of holes edge machining like T&G, chamfer and rebate on request.
Other data	Detailed technical values can be found in Koskisen's Declaration of Performance (DoP). Please visit Koskisen website.

Pallet sizes (pcs / pll)

KoskiPan stock products are marked with **P2**, **P5** or **P2Mr**. Stock products are available in pallets, special dimensions needs to be separately agreed.

mm	1220 x 2630 mm	1290 x 3045 mm	1830 x 2630 mm
6	100	100	50
8	80	80	80
9	80	80	70
10	70	70	70
12	60	60 P2	60
15	48	48 P2	40 P2
16	45	45 P2, P5, P2Mr	40 P2
18	40	40 P2, P5, P2Mr	40 P2
19	37	38 P2	38
22	33	33 P2, P5	30
25	29	29 P2, P5	25 P2
28	26	26 P2, P5 P2Mr	20
30	24	24	20
34	22	22	20
36	20	20	16
38	17	17 P2	14 P2
40	16	16	14

Sustainability

Koskisen's products are safe for their intended use and meet the quality, environment and product specific requirements set for them. Product development emphasises the development of responsible and sustainable product features. The focus is on improving the long-term use, renewability, safety, and traceability of products. Read more: koskisen.com/sustainability

Additional information

Koskisen chipboard is made from our own sawmill's sawdust and contains 90% real wood. Our professional quality control ensures that Koskisen chipboard is always pure

and does not include sand or other impurities. Pure and high-quality chipboard is easy to machine and it doesn't damage saw blades.

The information, although based on extensive testing, is intended as a guideline only and comes without warranty. We reserve the right to amend specifications without notice. Any defects other than those caused by clearly verified production or service faults by the supplier are the responsibility of the user. Any claim for compensation is limited to the value of the defective panels. The Seller makes no guarantee that the goods are fit for a particular purpose, unless it provides a written declaration of their suitability.



Koskisen Panel Industry

Tehdastie 2, 16600 Järvelä, FINLAND
tel. +358 20 553 41
www.koskisen.com

